

Class C Solutions Group

A business of MSC Industrial Supply Co.

Safety Data Sheet

Supply Co. - LOCTITE LB 771 NICKLE GRADE ANTI-SEIZE KNOWN AS NICKEL GRADE ANTI-SEIZE, 77124

Document Nbr: 077867
Class C Parts IDs 77124,77164

SAFETY DATA SHEET

HENKEL

REVISION NUMBER: 004.0

ISSUE DATE: 08/28/2014

-----1. PRODUCT AND COMPANY IDENTIFICATION -----

PRODUCT NAME:

LOCTITE LB 771 NICKLE GRADE ANTI-SEIZE KNOWN AS NICKEL GRADE ANTI-SEIZE

IDH NUMBER: 235028

PRODUCT TYPE: LUBRICANT

ITEM NUMBER: 77124

RESTRICTION OF USE: NONE IDENTIFIED

REGION: UNITED STATES

COMPANY ADDRESS:

HENKEL CORPORATION

ONE HENKEL WAY

ROCKY HILL, CONNECTICUT 06067

CONTACT INFORMATION:

TELEPHONE: (860) 571-5100

MEDICAL EMERGENCY PHONE:

POISON CONTROL CENTER: 1-877-671-4608 (TOLL FREE) OR 1-303-592-1711

TRANSPORT EMERGENCY PHONE:

CHEMTREC: 1-800-424-9300 (TOLL FREE) OR 1-703-527-3887

INTERNET: WWW.HENKELNA.COM

-----2. HAZARDS IDENTIFICATION -----

EMERGENCY OVERVIEW:

WARNING:

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

SUSPECTED OF CAUSING CANCER.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	2

PICTOGRAM(S):

HEALTH HAZARD

EXCLAMATION MARK

PRECAUTIONARY STATEMENTS:

PREVENTION:

OBTAIN SPECIAL INSTRUCTIONS BEFORE USE. DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD. AVOID BREATHING DUST OR FUMES. WASH THOROUGHLY AFTER HANDLING. CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE. WEAR EYE AND FACE PROTECTION. WEAR PROTECTIVE GLOVES. USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED.

RESPONSE:

IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO REMOVE. CONTINUE RINSING.

IF EXPOSED OR CONCERNED: GET MEDICAL ATTENTION.

IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ATTENTION.

IF EYE IRRITATION PERSISTS:

GET MEDICAL ATTENTION. TAKE OFF CONTAMINATED CLOTHING.

STORAGE: STORE LOCKED UP.

DISPOSAL:

DISPOSE OF CONTENTS AND/OR CONTAINER ACCORDING TO FEDERAL, STATE/PROVINCIAL AND LOCAL GOVERNMENTAL REGULATIONS.

CLASSIFICATION COMPLIES WITH OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) AND IS CONSISTENT WITH THE PROVISIONS OF THE UNITED NATIONS GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELING OF CHEMICALS (GHS).

SEE SECTION 11 FOR ADDITIONAL TOXICOLOGICAL INFORMATION.

-----3. COMPOSITION / INFORMATION ON INGREDIENTS -----

HAZARDOUS COMPONENT(S)	CAS NUMBER	PERCENTAGE*
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	30 - 60
NICKEL	7440-02-0	10 - 30
GRAPHITE	7782-42-5	5 - 10
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	1 - 5
ALUMINUM NOT POWDER, DUST OR FUME	7429-90-5	1 - 5
DISTILLATES (PETROLEUM), STRAIGHT-RUN MIDDLE	64741-44-2	0.1 - 1

* EXACT PERCENTAGE IS A TRADE SECRET. CONCENTRATION RANGE IS PROVIDED TO ASSIST USERS IN PROVIDING APPROPRIATE PROTECTIONS.

-----4. FIRST AID MEASURES -----

INHALATION:

MOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION.
IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.

SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING AND FOOTWEAR. IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER (USING SOAP, IF AVAILABLE). IF SYMPTOMS DEVELOP AND PERSIST, GET MEDICAL ATTENTION. WASH CLOTHING BEFORE REUSE.

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.
GET MEDICAL ATTENTION.

INGESTION:

ASPIRATION MAY CAUSE PULMONARY EDEMA AND PNEUMONITIS. DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET

MEDICAL ATTENTION.

SYMPTOMS: SEE SECTION 11.

NOTES TO PHYSICIAN:

ASPIRATION MAY CAUSE PULMONARY EDEMA OR ASPIRATION PNEUMONIA.

-----5. FIRE FIGHTING MEASURES -----

EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

SPECIAL FIREFIGHTING PROCEDURES:

WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING, SUCH AS TURN-OUT GEAR. IN CASE OF FIRE, KEEP CONTAINERS COOL WITH WATER SPRAY.

UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE

HAZARDOUS COMBUSTION PRODUCTS:

METAL VAPORS. OXIDES OF CARBON. OXIDES OF ALUMINUM. OXIDES OF NICKEL.

-----6. ACCIDENTAL RELEASE MEASURES -----

USE PERSONAL PROTECTION RECOMMENDED IN SECTION 8, ISOLATE THE HAZARD AREA AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL.

ENVIRONMENTAL PRECAUTIONS: DO NOT ALLOW PRODUCT TO ENTER SEWER OR WATERWAYS.

CLEAN-UP METHODS:

REFER TO SECTION 8 "EXPOSURE CONTROLS / PERSONAL PROTECTION" PRIOR TO CLEAN UP. SCRAPE UP AS MUCH MATERIAL AS POSSIBLE. STORE IN A PARTLY FILLED, CLOSED CONTAINER UNTIL DISPOSAL.

-----7. HANDLING AND STORAGE -----

HANDLING:

USE ONLY WITH ADEQUATE VENTILATION. PREVENT CONTACT WITH EYES, SKIN AND CLOTHING. DO NOT BREATHE VAPOR AND MIST. WASH THOROUGHLY AFTER HANDLING. KEEP CONTAINER CLOSED.

STORAGE:

KEEP IN A COOL, WELL VENTILATED AREA AWAY FROM HEAT, SPARKS AND OPEN FLAME. KEEP CONTAINER TIGHTLY CLOSED UNTIL READY FOR USE.

FOR INFORMATION ON PRODUCT SHELF LIFE CONTACT HENKEL CUSTOMER SERVICE AT (800) 243-4874.

-----8. EXPOSURE CONTROLS / PERSONAL PROTECTION -----

EMPLOYERS SHOULD COMPLETE AN ASSESSMENT OF ALL WORKPLACES TO DETERMINE THE

NEED FOR, AND SELECTION OF, PROPER EXPOSURE CONTROLS AND PROTECTIVE EQUIPMENT FOR EACH TASK PERFORMED.

HAZARDOUS COMPONENT(S)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	5 MG/M3 TWA MIST 10 MG/M3 STEL MIST	5 MG/M3 TWA MIST 500 PPM (2,000 MG/M3) PEL 5 MG/M3 PEL MIST.	NONE	NONE
NICKEL	1.5 MG/M3 TWA INHALABLE FRACTION.	1 MG/M3 PEL (AS Ni)	NONE	NONE
GRAPHITE	2 MG/M3 TWA RESPIRABLE FRACTION.	5 MG/M3 PEL RESPIRABLE FRACTION. 15 MG/M3 PEL TOTAL DUST. 15 MPPCF TWA	NONE	NONE
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	5 MG/M3 TWA MIST 10 MG/M3 STEL MIST	5 MG/M3 TWA MIST	NONE	NONE
ALUMINUM NOT POWDER, DUST OR FUME	NONE	NONE	NONE	NONE
DISTILLATES (PETROLEUM), STRAIGHT-RUN MIDDLE	5 MG/M3 TWA MIST 10 MG/M3 STEL MIST	5 MG/M3 TWA MIST	NONE	NONE

ENGINEERING CONTROLS:

USE POSITIVE DOWN-DRAFT EXHAUST VENTILATION IF GENERAL VENTILATION IS INSUFFICIENT TO MAINTAIN VAPOR CONCENTRATION BELOW ESTABLISHED EXPOSURE LIMITS.

RESPIRATORY PROTECTION:

OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE (29 CFR 1910.134). USE A NIOSH APPROVED SUPPLIED AIR RESPIRATOR WITH AN ORGANIC CARTRIDGE IF THE POTENTIAL TO EXCEED ESTABLISHED EXPOSURE LIMITS EXISTS.

EYE/FACE PROTECTION:

SAFETY GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS. SAFETY SHOWERS AND EYE WASH STATIONS SHOULD BE AVAILABLE.

SKIN PROTECTION: NEOPRENE OR OIL RESISTANT GLOVES.

-----9. PHYSICAL AND CHEMICAL PROPERTIES -----

PHYSICAL STATE: PASTE

COLOR: GRAY

ODOR: PETROLEUM

ODOR THRESHOLD: NOT AVAILABLE.

PH: NOT AVAILABLE.

VAPOR PRESSURE: <5 MMHg (80 DEG. F (26.7 DEG. C))

BOILING POINT/RANGE: NOT AVAILABLE.

MELTING POINT/RANGE: NOT AVAILABLE.

SPECIFIC GRAVITY: 1.1

VAPOR DENSITY: NOT AVAILABLE.

FLASH POINT: >93 DEG. C (>199.4 DEG. F)

FLAMMABLE/EXPLOSIVE LIMITS - LOWER: NOT AVAILABLE.

FLAMMABLE/EXPLOSIVE LIMITS - UPPER: NOT AVAILABLE.

AUTOIGNITION TEMPERATURE: NOT AVAILABLE.

EVAPORATION RATE: NOT AVAILABLE.

SOLUBILITY IN WATER: NEGLIGIBLE

PARTITION COEFFICIENT (N-OCTANOL/WATER): NOT AVAILABLE.

VOC CONTENT: 2.47%; 27 G/L

VISCOSITY: NOT AVAILABLE.

DECOMPOSITION TEMPERATURE: NOT AVAILABLE.

-----10. STABILITY AND REACTIVITY -----

STABILITY: STABLE UNDER NORMAL CONDITIONS OF STORAGE AND USE.

HAZARDOUS REACTIONS: WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

OXIDES OF CARBON. OXIDES OF ALUMINUM. OXIDES OF NICKEL.

INCOMPATIBLE MATERIALS: STRONG OXIDIZING AGENTS.

REACTIVITY: NOT AVAILABLE.

CONDITIONS TO AVOID: KEEP AWAY FROM HEAT, SPARK AND FLAME.

-----11. TOXICOLOGICAL INFORMATION -----

RELEVANT ROUTES OF EXPOSURE: SKIN, INHALATION, EYES, INGESTION

POTENTIAL HEALTH EFFECTS/SYMPTOMS:

INHALATION:

VAPORS MAY CAUSE HEADACHES, NAUSEA, DIZZINESS AND RESPIRATORY TRACT IRRITATION.

SKIN CONTACT: CAUSES SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION.

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION.

INGESTION:

INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

HAZARDOUS COMPONENT(S)	LD50S AND LC50S	IMMEDIATE AND DELAYED HEALTH EFFECTS	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	NONE	IRRITANT	
NICKEL	NONE	NO DATA	
GRAPHITE	NONE	LUNG	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	NONE	IRRITANT	
ALUMINUM NOT POWDER, DUST OR FUME	NONE	CENTRAL NERVOUS SYSTEM, IRRITANT, LUNG	
DISTILLATES (PETROLEUM), STRAIGHT-RUN MIDDLE	NONE	IRRITANT	
HAZARDOUS COMPONENT(S)	NTP CARCINOGEN	IARC CARCINOGEN	OSHA CARCINOGEN (SPECIFICALLY REGULATED)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	NO	NO	NO
NICKEL	REASONABLY ANTICIPATED	GROUP 2B	NO

TO BE A HUMAN
CARCINOGEN.

GRAPHITE	NO	NO	NO
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	NO	NO	NO
ALUMINUM NOT POWDER, DUST OR FUME	NO	NO	NO
DISTILLATES (PETROLEUM), STRAIGHT-RUN MIDDLE	NO	NO	NO

-----12. ECOLOGICAL INFORMATION -----

ECOLOGICAL INFORMATION: NOT AVAILABLE.

-----13. DISPOSAL CONSIDERATIONS -----

INFORMATION PROVIDED IS FOR UNUSED PRODUCT ONLY.

RECOMMENDED METHOD OF DISPOSAL:

FOLLOW ALL LOCAL, STATE, FEDERAL AND PROVINCIAL REGULATIONS FOR DISPOSAL.

HAZARDOUS WASTE NUMBER: NOT A RCRA HAZARDOUS WASTE.

-----14. TRANSPORT INFORMATION -----

THE TRANSPORT INFORMATION PROVIDED IN THIS SECTION ONLY APPLIES TO THE
MATERIAL/FORMULATION ITSELF, AND IS NOT SPECIFIC TO ANY PACKAGE/CONFIGURATION.

U.S. DEPARTMENT OF TRANSPORTATION GROUND (49 CFR):

PROPER SHIPPING NAME: NOT REGULATED

HAZARD CLASS OR DIVISION: NONE

IDENTIFICATION NUMBER: NONE

PACKING GROUP: NONE

INTERNATIONAL AIR TRANSPORTATION (ICAO/IATA):

PROPER SHIPPING NAME: NOT REGULATED

HAZARD CLASS OR DIVISION: NONE

IDENTIFICATION NUMBER: NONE

PACKING GROUP: NONE

WATER TRANSPORTATION (IMO/IMDG):

PROPER SHIPPING NAME: NOT REGULATED

HAZARD CLASS OR DIVISION: NONE

IDENTIFICATION NUMBER: NONE

PACKING GROUP: NONE

-----15. REGULATORY INFORMATION -----

UNITED STATES REGULATORY INFORMATION:

TSCA 8(B) INVENTORY STATUS:

ALL COMPONENTS ARE LISTED OR ARE EXEMPT FROM LISTING ON THE TOXIC SUBSTANCES CONTROL ACT INVENTORY.

TSCA 12(B) EXPORT NOTIFICATION: NONE ABOVE REPORTING DE MINIMIS

CERCLA/SARA SECTION 302 EHS: NONE ABOVE REPORTING DE MINIMIS

CERCLA/SARA SECTION 311/312: DELAYED HEALTH, IMMEDIATE HEALTH

CERCLA/SARA SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 (40 CFR 372). NICKEL (CAS# 7440-02-0).

CERCLA REPORTABLE QUANTITY:

NICKEL (CAS# 7440-02-0): 100 LBS. (45.4 KG)

CALIFORNIA PROPOSITION 65:

THIS PRODUCT CONTAINS A CHEMICAL KNOWN IN THE STATE OF CALIFORNIA TO CAUSE CANCER.

CANADA REGULATORY INFORMATION:

CEPA DSL/NDL STATUS:

ALL COMPONENTS ARE LISTED ON OR ARE EXEMPT FROM LISTING ON THE CANADIAN DOMESTIC SUBSTANCES LIST.

-----16. OTHER INFORMATION -----

THIS SAFETY DATA SHEET CONTAINS CHANGES FROM THE PREVIOUS VERSION IN SECTIONS:
NEW SAFETY DATA SHEET FORMAT.

PREPARED BY: LOU FABRIZIO, REGULATORY AFFAIRS SPECIALIST

ISSUE DATE: 08/28/2014

DISCLAIMER:

THE DATA CONTAINED HEREIN ARE FURNISHED FOR INFORMATION ONLY AND ARE BELIEVED TO BE RELIABLE. HOWEVER, HENKEL CORPORATION AND ITS AFFILIATES ("HENKEL") DOES NOT ASSUME RESPONSIBILITY FOR ANY RESULTS OBTAINED BY PERSONS OVER WHOSE METHODS HENKEL HAS NO CONTROL. IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE SUITABILITY OF HENKEL'S PRODUCTS OR ANY PRODUCTION METHODS MENTIONED HEREIN FOR A PARTICULAR PURPOSE, AND TO ADOPT SUCH PRECAUTIONS AS MAY BE ADVISABLE FOR THE PROTECTION OF PROPERTY AND PERSONS AGAINST ANY HAZARDS THAT MAY BE INVOLVED IN THE HANDLING AND USE OF ANY HENKEL'S PRODUCTS.

IN LIGHT OF THE FOREGOING, HENKEL SPECIFICALLY DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARISING FROM SALE OR USE OF HENKEL'S PRODUCTS. HENKEL FURTHER DISCLAIMS ANY LIABILITY FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OF ANY KIND, INCLUDING LOST PROFITS.