# **Safety Data Sheet**

# Section 1 - Product and Company Identification

Product Name: SYN TECH 150

Trade Name: Industrial Oil

Benz Oil Company 2724 W. Hampton Ave. Milwaukee, WI 53209 Product Code: 425020

**Telephone Numbers** 

During normal business hours call (414)442-2900

Outside normal business hours call CHEMTREC (800)424-9300

Email Address msds@benz.com

Product Use: Industrial Lubricant

Not recommended for: Applications other than those intended. For application information see product Technical

Data Sheet or consult with a company representative.

# Section 2 - Hazards Identification

### **Emergency Overview:**

In accordance with good industrial hygiene and industrial practices. Airborne exposures should be controlled to the lowest extent possible. Do not ingest. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash thoroughly after handling. Keep container closed.

GHS Ratings: This product is not hazardous according to OSHA 29CFR 1910.1200

### **GHS Hazards**

### **GHS Precautions**

There are no GHS ratings that apply to this product at this time.

# Section 3 - Composition

\*Proprietary additive(s) listed only if considered hazardous per OSHA regulations, at a 1% or greater concentration (0.1% for carcinogens)\*

Chemical Name	CAS number	Weight Concentration %
Synthetic Base Stock	TS-217	60.00 - 70.00
Synthetic Base stock	TS-215	10.00 - 20.00

# Section 4 - First Aid Measures

### Inhalation:

Remove from further exposure. For those providing assistance, avoid exposure to yourself. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, a trained individual should attempt to resuscitate while getting immediate medical aid.

### Eye Contact:

Page 1 of 5

Printed: 5/12/2015 at 9:41:09AM

Flush eyes with water for at least 15 minutes. If irritation occurs, seek medical attention.

### **Skin Contact:**

Prolonged or repeated contact may cause irritation. Good hygienic practices should be observed at all times. Wash exposed skin with soap and warm water.

### Ingestion:

First aid is not normally required. Seek medical attention if discomfort occurs. Do not induce vomiting unless directed to do so by medical personnel.

# Section 5 - Fire Fighting Measures

Flash Point: 232 C (450 F)

### Extinguishing Media:

Carbon Dioxide (CO2), dry chemical or foam. Water can be used to cool and protect exposed material.

### Unusual Fire Hazards:

Pressurized mists may form a flammable mixture.

### **Products of Combustion:**

Fumes, smoke, COx, SOx, NOx, when combusted.

### Fire Fighting Instructions:

Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Fire fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water supply to cool fire exposed surfaces and to protect personnel.

# Section 6 - Accidental Release Measures

### **Notification Procedures:**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material (which exceed the applicable reportable quantity) into the environment, or oil spills which could reach any waterway (including intermittent dry creeks). The National Response Center can be reached at 1-800-424-8802.

### **Spill Management:**

Shut off source of leak if it is safe to do so. Dike and contain spill.

### Small Spills

While wearing suitable personal protective equipment (PPE), absorb spill with clay, sand or other suitable material. Place in a non-leaking container and seal tightly for proper disposal.

### Large Spills:

Ventilate the contaminated area. Wearing suitable PPE, pump into salvage vessels. Dispose of collected material according to regulations.

### Section 7 - Handling and Storage

### Handling:

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Do not take internally. Use this product with adequate ventilation. Launder work clothes frequently.

### Storage

Keep properly labeled container tightly closed, and in a cool, well-ventilated place away from incompatible materials. Store away from heat, sparks and other ignition sources. Containers, even those have been emptied, can contain combustible vapors. Do not pressurize, cut, weld, drill or grind on or near containers. Do not reuse empty containers.

# Section 8 - Exposure Controls / Personal Protection

	Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
--	-------------------------	----------------------	-----------------------	-----------------------

SDS for: 425020

Synthetic Base Stock TS-217	PEL: 5 mg/m3 (mists and aerosols)	TLV: 5 mg/m3 (mists and aerosols)	Not Determined
Synthetic Base stock TS-215	PEL: 5 mg/m3 (mists and aerosols)	TLV: 5 mg/m3 (mists and aerosols)	Not Determined

### **Ventilation Control:**

Provide adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

### Personal Protection:

As prescribed in the OSHA Standard for Personal Protective Equipment (29 CFR 1910.132), employers must perform a Hazard Assessment of all workplaces to determine the need for proper protective equipment for each employee .

### **Eve Protection:**

Normal industrial eye protection practices should be employed.

### Skin Protection:

In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

### Respiratory:

If airborne concentration limits are not met, a NIOSH approved respirator must be worn.

### Contaminated Gear:

Soiled work clothing should be laundered or dry-cleaned.

# Section 9 - Physical and Chemical Properties

Typical physical and chemical properties are given below. Consult the manufacturer in Section 1 for additional data.

Appearance: Clear Straw Colored

Liquid

Vapor Pressure: No Data Available

Vapor Density: No Data Available

Specific Gravity@60F 0.9

Freezing point: No Data Available

Flash point: 450 F, 232 C

Flammability: No Data Available

Partition coefficient (n-

octanol/water): No Data Available

Decomposition temperature: No Data Available

Odor: Characteristic

Odor threshold: No Data Available

pH: Not Applicable

Melting point: No Data Available

Solubility: Negligible Solubility in

Water

Evaporation rate: No Data Available

Explosive Limits: No Data Available

Autoignition temperature: No Data Available

Grams VOC less water: No Data Available

# Section 10 - Stability and Reactivity

### Stability:

Material is stable under normal conditions.

### **Conditions to Avoid:**

Excessive heat. High energy sources of ignition.

### Material to Avoid:

Strong oxidizers.

# **Hazardous Decomposition Products:**

This material does not decompose at ambient temperatures.

### Hazardous Polymerization:

Will not occur under normal circumstances.

# Section 11 - Toxicological Information

### **Mixture Toxicity**

Oral Toxicity LD50: 2,301mg/kg Dermal Toxicity LD50: 2,022mg/kg Inhalation Toxicity LC50: 25mg/L

### **Component Toxicity**

TS-217

Synthetic Base Stock

Oral LD50: >2,000 mg/kg (Rat) Dermal LD50: >2,000 mg/kg (Rabbit)

TS-215

Synthetic Base stock

Oral LD50: >2,000 mg/kg (Rat) Dermal LD50: >2,000 mg/kg (Rabbit)

If applicable, the ingredient(s) listed above are considered hazardous per OSHA 1910.1200. Included are the corresponding LD50 ratings, if available. Hazardous ingredients are required to be listed if they are used in the final product at a 1% (0.1% for carcinogens) or greater concentration.

Routes of Entry: Eye contact. Dermal contact. Inhalation. Ingestion.

Target Organs: None Known

# Section 12 - Ecological Information

### **Ecotoxicity:**

No data available for this product.

# Section 13 - Disposal Considerations

### Disposal Instructions:

Refer to the latest US EPA, state and local regulations regarding proper disposal.

# Section 14 - Transport Information

<u>Agency</u>

**Proper Shipping Name** 

Not Regulated

**UN Number** 

N/A

Packing Group

N/A

**Hazard Class** 

N/A

# Section 15 - Regulatory Information

Prepared according to US OSHA 29CFR 1910.1200 regulations.

Additional regulatory listings, where applicable.

**California Prop 65:** The following chemicals are known to the State of California to cause cancer, birth defects, or other reproductive harm.

91-20-3 Naphthalene PROP65 Trace Chemical

### Toxic Substances Control Act (TSCA) Status:

All components are listed on the EPA/TSCA Inventory of Chemical Substances unless listed below.

- None

SDS for: 425020


Printed: 5/12/2015 at 9:41:09AM

# Section 16 - Other Information

### Hazardous Material Information System (HMIS)

# HEALTH 1 FLAMMABILITY 1 PHYSICAL HAZARD PERSONAL PROTECTION 1 HMIS & NFPA Hazard Rating Legend \* = Chronic Health Hazard 0 = INSIGNIFICANT 1 = SLIGHT 2 = MODERATE 3 = HIGH

**National Fire Protection Association (NFPA)** 



Date Prepared: 5/12/2015

Benz Oil Company has taken all reasonable steps to insure this data sheet and the information contained in it is accurate as of the date issued. No warranty is made as to the accuracy or completeness of the information in this data sheet. The information stated on this MSDS applies only to the intended applications. Do not use this product for any application other than the intended application.

Employers are responsible for communicating any hazards and precautions described in this sheet.

Page 5 of 5

Printed: 5/12/2015 at 9:41:09AM